
# EXISTING PROPOSED PROPERTY LINE EASEMENT LINE EDGE OF GRAVEL CONTOURS EDGE OF WATER EDGE OF WETLAND WETLAND BOUNDARY FLAG RAPARIANI ZONIE WETLAND OFFSET / BUFFER FLOODPLAN TREE LINE UTLITY POLE FLOOD LIGHT AREA LIGHT OVERHEAD UTILITIES UNDERGROUND UTILITIES WATER RINE WATER RINE WATER RYDRANT SANITARY SEVER PS PS PROPOSED PROPOSED

## Site Development Plans Pool Area Jellystone Park Cranberry Acres 20 Shoestring Road Carver, MA

**September 20, 2022** 





LOCATION PLAN

PREPARED FROM: BING MAPS SCALE: 1"= 1 MILE (5280 FEET)

OTE

HIS DI AN WAS PREPARED FROM THE PLAN OF REFERENCE AND THE ASSESSORS MAPS OF THE TOWN OF CARVER

### SHEET INDEX

SHEET NUMBER	DESCRIPTION	REVISION NUMBER	DATE
1	TITLE SHEET		9/20/2022
2	EXISTING CONDITIONS - POOL AREA		9/20/2022
3	DEMOLITION PLAN - POOL AREA		9/20/2022
4	SITE PLAN - POOL AREA		9/20/2022
5	GRADING & UTILITY PLAN - POOL AREA		9/20/2022
6	LANDSCAPE PLAN - POOL AREA		9/20/2022
7	EROSION CONTROL DETAILS - POOL AREA		9/20/2022
8	CONSTRUCTION DETAILS - POOL AREA		9/20/2022
9	CONSTRUCTION DETAILS - POOL AREA		9/20/2022
DD-1.4	ADG - LANDSCAPE PLAN	8 .	9/20/2022

No.	Revision		Date
De	signed by:	Drawn by: DMF	Checked by:

Title Sheet

Jellystone Park Cranberry Acres
20 Shoestring Road
Carver, MA

Assessors Map 124 Lot 13, Map 125 Lot 3A



(603) 647-8700 www.sfceng.com

Sheet 1 of 9

SITE PLAN APPROVAL

CARVER PLANNING BOARD

Scale: 1" = 250' ±


Date: 9/20/2022


THOP MAGO


NGR Cape Cod, LLC 38 Commerce Ave. SW Suite 200 Grand Rapids, MI 4950


Zoning Classification: Residential Agricultural


Desires SESDED ICA THE Legal Title














- UTES
  MPORARY SEDIMENT TRAPS SHALL COMPLY WITH THE FOLLOWING:
  THE TRAP SHALL BE INSTALLED AS CLOSE TO THE DISTURBED AREA OR
  SOURCE OF SEDIMENT AS POSSIBLE;
  THE MAXIMUM CONTRIBUTING DRAININGE AREA TO THE TRAP SHALL BE

- (b) THE MAXIMUM CONTRIBUTING ORANIAGE AREA TO THE TRAP SHALL BE LESS THAN S ACRES;
  (c) THE MAXIMUM VOLUME OF THE TRAP SHALL BE 3,000 CUBIC FEET OF STORAGE FOR EACH ACRE OF DRAINAGE AREA;
  (d) THE SIDE SLOPES OF THE TRAP SHALL BE 3.1 OR FLATTER, AND SHALL BE STABLIZED MIMEDIATELY AFTER THEIR CONSTRUCTION;
  (e) THE OUTLET OF THE TRAP BHALL BE A MINIMUM OF ONE FOOT BELOW THE CREST OF THE TRAP AND SHALL BIS AMRIED TO A STABLIZED AREA;
  (f) THE TRAP SHALL BE CLEARED WHEN SO FERCENT OF THE ORIGINAL VOLUME IS PILL D). AND
  (g) THE INACETIALS REMOVED FROM THE TRAP SHALL BE PROPERLY DISPOSED OF AND STABLIZED.


- SPECIFICATIONS
  TEMPORARY SEDIMENT TRAPS SHALL BE DESIGNED IN ACCORDANCE WITH
  MASSACHUSETTS STORMWATER HANDBOOK.

  (a) SEDIMENT TRAPS SHOULD BE LOCATED SO THAT THEY CAN BE INSTALLED
  PRIOR TO DISTURBING THE AREA THEY ARE TO PROTECT.

  (b) THE MAXIMUM HEIGHT OF THE SEDIMENT TRAP EMBAINMENT SHOULD BE 4
  FEET WHEM MEASURED FROM THE LOWEST FORM TO HATURAL GROUND

- THE LYMEL MILESONED FROM THE LOWES FORTH OF THE THE AUGUST AND THE OWN OF THE MANAGEMENT AND THE AUGUST AND THE CHARACTER OF THE EMBANGUEST IS A MINIMAL OF THE OWN THE CREST ELEVATION OF THE OWN THE

### **TEMPORARY SEDIMENT TRAPS**



### CONSTRUCTION SPECIFICATIONS

- STONE FOR A STABILIZED CONSTRUCTION EXIT SHALL BE MINIMUM 3 INCH
- CRUSHED STONE.
  THE MINIMUM LERIGH OF THE PAD SHOULD BE 75 FEET, EXCEPT THAT THE
  MINIMUM LENGTH MAY BE REDUCED TO 50 FEET IF A 3-NICH TIG-HICH HIGH
  BERM IS INSTALLED AT THE ENTRAINCE OF THE PROJECT SITE.
  THE THICKNESS OF THE STONE FOR THE STABILIZED EXIT SHALL NOT BE LESS

- THE PAD SHOULD EXTEND THE FULL WIDTH OF THE CONSTRUCTION ACCESS

- THE PAD SHOULD EXTRID THE FULL WIDTH OF THE CONSTRUCTION ACCESS ROAD OR 10 FEET, WHICHEVER IS GREATER,
  GEOTEXTILE FILTER CLOTH SHALL BE PLACED OVER THE ENTIRE AREA PRIOR TO PLACING THE STONE.

  ALL SURFACE WATER SHALL BE DIRECTED AWAY FROM THE EXIT. IF WATER IS FLOWNS TO SWARD THE EXIT, A BERN WITH 5-1 SLOPES THAT CAN BE CROSSED BY VEHICLES MAY BE ADDED.

  THE PAD SHOULD BE MAINTAINED OR REPLACED WHEN MUD AND SO IL PARTICLES ACE TRACED OF THE CONTROL PAD DECOMES BIFFEETURE AND MUD AND SOIL PRATICLES ARE TRACED OF FIRE.

  NATURAL DRAINAGE THAT CROSSES THE LOCATION OF THE STONE PAD SHOULD BE INTERCEPTED AND PIPED BEINETH THE PAD, AS NECESSARY, WITH SUITABLE OUTLET PROTECTION.

### MAINTENANCE

- ALINITEMANCE
  WHEN THE CONTROL PAD BECOMES INEFFECTIVE. THE STONE SHOULD BE
  REMOYED ALONG WITH THE COLLECTED SOIL MATERIAL, REGRADED ON SITE
  AND STABLIZED. THE EXIT SHOULD THEN BE RECONSTRUCTED.
  THE CONTRACTOR SHOULD. SWEEP THE PAYEMENT AT EXITS WHENEVER SOIL
  MATERIALS ARE TRACKED ONTO THE ADJACENT PAYEMENT OR TRAVELED WAY.
  WHEN WHELE WASHING IS REQUIRED, IT SHOULD BE CONDUCTED ON AN AREA
  STABILIZED WITH AGGREGATE, WHICH DRAINS NTO AN APPROVED
  SEDIMENT-TAPPING DEVICE, ALL SEDIMENT SHOULD BE PREVENTED FROM
  ENTERING STORM DRAINS, DITCHES, OR WATERWAYS.

### **TEMPORARY GRAVEL CONSTRUCTION EXIT**

- NOTES
  1. ALL MATERIAL TO MEET FILTREXX™ SPECIFICATIONS.
- THE CONTRACTOR SHALL MAINTAIN THE COMPOST FILTER
  BERM IN A FUNCTIONAL CONDITION AT ALL TIMES AND IT
  SHALL BE ROUTINELY INSPECTED.
- WHERE THE BERM REQUIRES REPAIR, IT WILL BE ROUTINELY REPAIRED.
- 4. THE CONTRACTOR SHALL REMOVE SEDIMENTS COLLECTED AT THE BASE OF THE BERM WHEN THEY REACH 1/3 OF THE EXPOSED HEIGHT OF THE BERM, OR AS DIRECTED BY THE ENGINEER.
- 5. THE COMPOST FILTER BERM WILL BE DISPERSED ON SITE WHEN NO LONGER REQUIRED, AS DETERMINED BY THE ENGINEER.

### SOCK OPTION: FILTREXXIN FILTER SOCK, SIZED TO SUIT CONDITIONS. 300mm TO 450mm (12\* TO 18\*) TYPICAL. SILT SOCK OR MULCH BERN WATER FLOW

### FILTER COMPOST MATERIAL AS PER SPECIFICATIONS. TYPICAL BERM FOR MINIMAL GRADES SHOWN. FOR STEEPER GRADES, I.E. 2:1 SLOPES INCREASE BERM SIZE AS DETERMINED ON SITE BY ENGINEER. AREA TO BE PROTECTED WORK AREA

### SILT SOCK INSTALLATION DETAIL

### TEMPORARY SEEDING SPECIFICATIONS

REFERENCE MASSACHUSETTS EF

### A) SITE PREPARATION

- 1. INSTALL NEEDED EROSION AND SEDIMENT CONTROL MEASURES SUCH AS SILTATION BARRIERS. DIVERSIONS, AND SEDIMENT TRAPS.
- 2. GRADE AS NEEDED FOR THE ACCESS OF EQUIPMENT FOR SEEDBED PREPARATION, SEEDING, MULCH
- APPLICATION, AND MULCH ANCHORING
- 3. RUNOFF SHOULD BE DIVERTED FROM THE SEEDED AREA.
- ON SLOPES 4:1 OR STEEPER, THE FINAL PREPARATION SHOULD INCLUDE CREATING HORIZONTAL GROOVES PERPENDICULAR TO THE DIRECTION OF THE SLOPE TO CATCH SEED AND REDUCE RUNOFF

### B) SEEDBED PREPARATION


- B) SEEDBED PREPARATION:


  1. STONES AND TRASH SHOULD BE REMOVED SO AS NOT TO INTERFERE WITH THE SEEDING AREA.

  2. WHERE THE SOIL HAS BEEN COMPACTED BY CONSTRUCTION OPERATIONS, LOOSEN SOIL TO A DEPTH OF 2 INCHES BEFORE APPLYING FERTILIZER, LIME AND SEED.

  3. FAPPLICABLE, FERTILIZER AND ORGANIC SOIL AMENDMENTS SHOULD BE APPLIED DURING THE GROWING SEASON. FERTILIZER SHALL ONLY BE USED BASED ON SOIL TEST RESULTS. FERTILIZER. SHALL BE RESTRICTED TO A ZERO PHOSPHATE, SLOW RELEASE NITROGEN FERTILIZER. NO FERTILIZER SHALL BE USED WITHIN THE PROTECTIVE WELL RADIUS, AND WITHIN 25 FEET OF A SURFACE WATER BODY. RATE OF APPLICATION SHALL BE PER MANUFACTURER AND SOIL TEST RESULTS.

- SELECT SEED FROM TABLE BELOW.
- 1. SELECT SEED FROM TABLE BELOW.
  2. APPLY SEED UNIFORMLY BY HAND, CYCLONE SEEDER, DRILL, CULTIPACKER TYPE SEEDER OR
  HYDROSEEDER (SLURRY INCLUDING SEED AND FERTILIZER). NORMAL SEEDING DEPTH IS FROM % TO %
  INCH. HYDROSEEDING THAT INCLUDES MULCH MAY BE LEFT ON SOIL SURFACE. SEEDING RATES MUST
  BE INCREASED 10 % WHEN INTROSEEDING.
  3. TEMPORARY SEEDING SHOULD TYPICALLY OCCUR PRIOR TO SEPTEMBER 15TH.
- 4. AREAS SEEDED BETWEEN MAY 15TH AND AUGUST 15TH SHOULD BE COVERED WITH HAY OR STRAW
- AREAS SEEDED BETWEEN MAY 15 HAND AUGUST 15 HIS MOULD BE COVERED WITH HAY ON STRAW
  MUICH, ACCORDING TO THE "ELMPORARY AND PERMANENT MUICHING" PRACTICE.
   VEGETATED GROWTH COVERING AT LEAST 65% OF THE DISTURBED AREA SHOULD BE ACHIEVED PRIOR
  TO OCTOBER 15 HI. IF HIS CONDITION IS NOT ACHIEVED, IMPLEMENT OTHER TEMPORARY
  STABILIZATION MEASURES FOR OVERWINTER PROTECTION.
   PROVIDE MUICH WHERE IT IS IMPRACTICAL TO INCORPORATE SEED INTO MOIST SOIL. THE SEEDED
  AREA SHOULD BE MUICHED TO FACILITATE GERMINATION. REFERENCE IN STORMWATER MANUAL:
  VOLUME 3 FOR TEMPORARY AND PERMANENT MUICHING REQUIREMENTS.





% OF WEIGHT SMALLER THAN THE GIVEN SIZE	SIZE OF STONE IN INCHES	OUTLET LOCATION	PIPE DIA. OR UPSTREAM WIDTH	w	La	d	d 50
100%	5.8			- 11		_	-
85%	3.7 TO 5.2	FES	12"	14'	11'	9.	2.9*
50%	2.9 TO 4.3						
15%	0.9 TO 1.4						

- THE SUBGRADE FOR THE GEOTEXTILE FABRIC AND RIP-RAP SHALL BE PREPARED TO THE LINES AND GRADES SHOWN ON THE PLANS.
- 2. THE ROCK USED FOR RIP-RAP SHALL CONFORM TO THE SPECIFIED GRADATION
- 3. GEOTEXTILE FABRICS SHALL BE PROTECTED FROM PUNCTURE OR TEARING DURING THE PLACEMENT OF THE ROCK RIP-RAP. DAMAGED AREAS IN THE FABRIC SHALL BE REPAIRED BY PLACING A PIECE OF FABRIC OVER THE DAMAGED AREA OR BY COMPLETE REPLACEMENT OF THE FABRIC. ALL OVERLAPS REQUIRED FOR REPAIRS OR JOINING TWO PIECES OF FABRIC SHALL BE A MINIMUM OF 12 INCHES.
- STONE FOR THE RIP-RAP MAY BE PLACED BY EQUIPMENT AND SHALL BE CONSTRUCTED TO THE FULL LAYER THICKNESS IN ONE OPERATION AND IN SUCH A MANNER AS TO PREVENT SEGREGATION OF THE STONE SIZES

**OUTLET APRON DETAIL** 

### CONSTRUCTION SEQUENCE

- INSTALL PERIMETER EROSION CONTROL MEASURES. TEMPORARY EROSION AND SEDIMENT CONTROL PRACTICES SHALL BE INSTALLED PRIOR TO ANY EARTH MOVING OPERATION. EROSION CONTROL MEASURES SHALL BE INSTALLED AS SHOWN ON THE PLAINS ADS SHALL CONFORM TO ALL APPLICABLE SECTIONS OF THE MASSACHUSETTS EROSION AND SEDIMENT CONTROL GUIDEDUNING. ON URBAN AND SUBBURBAN AREAS, MAY 2003. AND THE MASSACHUSETS STORMAYATER HANDBOOK AND STORMAYATER STANDARS, FEBRUARY 2003.
- 2. CUT AND CLEAR TREES, IDENTIFY TREES TO BE SAVED AND INSTALL PROTECTIVE FENCES AROUND THESE TREES, CUT TREES, CLEAR AND DISPOSE OF DEBRIS.
- 3. INSTALL OTHER EROSIOH CONTROL MEASURES. TEMPORARY AND PERMANENT EROSION, SEDIMENT AND DETENTION PRACTICES NCLUDING PORDS AND SYMLES SHALL BE INSTALLED PRIOR TO ROUGH GRADNIG, PERMANENT STORMWATER TREATMENT SYSTEMS. ARE TO BE CONSTRUCTED AND SEEDED AS SOON AS PRACTICALS OTHAT VEGETATION MAY BE ESTABLISHED PRIOR TO DIRECTING RUIGFET OT THEM. ADDITIONAL STORMWATER MANAGEMENT PRACTICES SHALL BE IMMEDIATELY INSTALLED WHEN NECESSARY AND APPROPRIATE DURING CONSTRUCTION.
- PROTECT DRAINAGE STRUCTURES. DURING CONSTRUCTION, ALL DRAINAGE INLETS SHALL BE PROTECTED BY INSTALLING A GEOTEXTILE BARRIER UNDER THE GRATE OR BY INSTALLING A STONE CHECK DAM AROUND THE PERIMETER OF THE GRATE.
- CLEAR AND GRUB, STRIP ORGANIC SOILS, LOAM SHALL BE STRIPPED FROM THE SITE AS REQUIRED. THE SMALLEST PRACTICAL AREA SHALL BE EXPOSED AT ANY TIME AND SHALL NOT EXCEED ONE ACRE, UNSTABILIZED SOIL SHALL BE TEMPORARILY STABILIZED AS SOON AS PRACTICABLE BUT NO LATER THAN 30 DAYS, AFTER INTIAL DISTURBANCE.
- STABILIZE STOCKPILES. SOIL STOCKPILES SHALL BE LOCATED AND PROTECTED TO MINIMIZE EROSION. INSTALL SILT FENCING AROUND THE BASE OF ALL STOCKPILES ON THE DOWNHLL SIDE.
- INSPECT AND MAINTAIN ALL EROSION CONTROL MEASURES. ALL PRACTICES ARE TO BE INSPECTED AND MAINTAINED THROUGHOUT THE CONSTRUCTION PERIOD ACCORDING TO RECOMMENDED SCHEDULED, BUT AT LEAST ONCE PER WEEK, AND DURING RAINFALL EVENTS IN WHICH IS INCHO PRECIDENTAIN OR MORE FALLS WHITHIN 24 HOUR PERIOD. THE BOTTOM OF SEDIMENT BASINS SHALL BE PERIODICALLY CLEANED, WITH SEDIMENT REMOVED TO A SECURE LOCATION. ALL DAMAGED SILT BARRIERS SHALL BE REPAIRED. SEDIMENT DEPOSITS SHALL BE PERIODICALLY REMOVED.
- GRADE AND GRAVEL AREAS TO BE PAVED. ROADWAYS AND PARKING LOTS SHALL BE GRADED, AND UNDERGROUND UTILITIES SHALL BE INSTALLED, GRAVEL SHALL BE INSTALLED AS SOON AS PRACTICE. I. HISSE AREAS SHALL BE STABILIZED WITHIN 72 HOURS OF ACHIEVING FIRISH ORDER. ALL FILL MATERIAL SHALL BE FREE FROM STUMPS, ROOTS, WOOD, ETC.
- STABILIZE DISTURBED AREAS. BEGIN SEED AND MULCH OF ALL DISTURBED AREAS AS SOON AS PRACTICAL, BUT NO LATER THAN THREE DAYS AFTER FINAL GRADING. ALL CUT AND FILL SLOPES SHALL BE SEEDED AND MULCHED WITHIN 72 HOURS OF ACHIEVING FINISHED GRADE. A NUMBUM OF 4" OF LOAM SHALL BE INSTALLED, WITH SEED, LUME, AND FERTILIZER APPLICATION.
- FINISH PAVING. INSTALL FINISH PAVING ON ROADWAYS AND PARKING LOTS.
- 11. COMPLETE PERMANENT SEEDING AND LANDSCAPING, SPREAD LOAM AND STABILIZE PER PLANS AND SPECIFICATIONS.

- 12. All AREA SHALL BE CONSIDERED STABLE IF ONE OF THE FOLLOWING HAS OCCURRED:

  1) BASE COURSE GRAVELS HAVE BEEN INSTALLED IN AREAS TO BE PAYED;

  1) A MINIMUM OF 85% VECEITATED GROWIN HAS BEEN ESTABLISHED.

  10) A MINIMUM OF 3° OF NON-ENOISYE MATERIAL SUCH AS STONE OR RIPPRAP HAS BEEN INSTALLED, OR

  1) EROSION CONTROL BLANKETS HAVE BEEN PROPERLY INSTALLED.
- REMOVE TEMPORARY EROSION CONTROL MEASURES. AFTER CONSTRUCTION IS COMPLETED AND THE AREAS ARE STABLUZED MANIMUM 85% VEGETATIVE COVER, BASE COURSE GRAVELS INSTALLED, 2º NON-EROSNE MATERIAL BISTALLED, OR EROSION CONTROL BUT

### 14. WINTER CONSTRUCTION NOTES

- WHITER CONSTRUCTION NOTES:

  IN ALL PROPOSED VEGETATED AREAS THAT DO NOT EXHBIT A MINIMUM OF 85% VEGETATIVE GROWTH BY NOVEMBER 30, OR WHICH ARE DISTURBED AFTER NOVEMBER 30, SHALL BE STABILIZED BY SEEDING AND INSTALLING EROSION CONTROL BLANKETS ON SLOPE GREATER THAN 13, AND SEEDING AND PLACENDS TO 14 O TONS OF MULCH PER ACCE, SECURED WITH ANCHORDEN DETTING, ELSEWHERE, THE INSTALLATION OF EROSION CONTROL BLANKETS OR MULCH AND NETTING SHALL NOT OCCUR OVER ACCUMULATED SNOW OR ON FROZEN GROUND AND SHALL BE COMPLETED IN ADVANCE OF THAN OR SERVING MELT EVENTS.

  IN ALL DIT CHES OR SMALLES WHICH DO NOT EXHIBIT A MINIMUM OF 85% VEGETATIVE GROWTH BY NOVEMBER 30, SHALL BE STABILIZED TELEPORRAIL WITH STADLE OR REDISSION CONTROL BLANKETS APPROPRIATE FOR THE DESIGN FLOW ON NOTIONS.

  IN AFTER KOVEMBER 30, INCOMPLETE ROAD OR PAYMING SURFACES, WHERE VORKI WAS STOPPED FOR THE WINTER SEASON, SHALL BE PROTECTED.
- 15. MINIMUM REQUIREMENTS: THE EROSION CONTROL MEASURES SHOWN ON THESE PLANS ARE THE MINIMUM NECESSARY DURING CONSTRUCTION. THE CONTRACTOR SHALL BE RESPONSIBLE FOR ENSURING THAT ADEQUATE EROSION CONTROL PRACTICES ARE EMPLOYED OF PREVENT EROSION AND SEMENTATION TO ADJACENT PROPERTIES, ROADS, OR DRAINAGE SYSTEMS.

### **DUST CONTROL NOTES**

- ON AS SOON AS POSSIBLE FOLLOWING EARTH DISTURBING ACTIVITIES
- 2. MOISTEN EXPOSED SOIL SURFACES AS NEEDED AT A RATE OF 300 GALLONS PER ACRE. AVOID EXCESSIVE WATER APPLICATION TO PREVENT RUNOFF AND PONDING.

PLANT SELECTION AND SEEDING RATES PER ACRE BUSHELS (BU) OR SPECIES POUNDS (LBS) PER 1,000 SE REMARKS 2 BU OR 112 LBS 2.5 LBS BEST FOR FALL SEEDING. SEED FROM AUGUST 15 TO SEPTEMBER 15 FOR BEST

OATS	2.5 BU OR 80 LBS	2 LBS	BEST FOR SPRING SEEDINGS. SEED NO LATER THAN MAY 15 FOR SUMMER PROTECTIONS. SEED TO A DEPTH OF 1 INCH.
ANNUAL RYEGRASS	40 LBS	1LB	GROWS QUICKLY, BUT IS OF SHORT DURATION. USE WHERE APPEARANCES ARE IMPORTANT. SEED EARLY SPRING AND/OR BETWEEN AUGUST IS AND SEPTEMBER 15. COVERT HE SEED WITH NO MORE THAN 0.25 INCH OF SOIL.
PERENNIAL RYEGRASS	30 LBS	0.7 LB	GOOD COVER VINICH IS LONGER LASTING THAN AVIIUAL RYEGRASS. SEED BETYVEEN APPRIA MALE MANDE TO BE TYPEEN AUGUST IS AND SEPTEMBER 15. MULCHING WAL ALLOW SEEDING THROUGHOUT THE GROWING SEASON. SEED TO A DEPTH OF APPROXIMATELY OS INGE.

Erosion Control Details - Pool Area **Jellystone Park Cranberry Acres** 20 Shoestring Road Carver, MA Assessors Map 124 Lot 13, Map 125 Lot 3A

Revision

183 Rockingham Rd, Unit 3 East ENGINEERING Scale: As Shown

Sheet 7 of 9

SITE PLAN APPROVAL

CARVER PLANNING BOARD

Prepared for: Suite 200

NGR Cape Cod, LLC 38 Commerce Ave. SW Grand Rapids, MI 49503

Zoning Classification: Residential Agricultural

Date

www.sfceng.com

Date: 9/20/2022

Drawn by: DMF

### **BERM CONSTRUCTION CRITERIA**

FOUNDATION PREPARATION
THE FOUNDATION AREA SHALL BE CLEARED OF TREES, LOGS, STUMPS, ROOTS, BRUSH, BOULDERS, SOD, AND
RUBBISH. TO ESTABLISH VEGETATION, THE TOPSOIL AND SOD SHALL BE STOCKPILED AND SPREAD ON THE
COMPLETED BERN AND SPILLWAYS FOUNDATION SURFACES SHALL BE SLOPED NO STEPER THAN 1:1. THE
FOUNDATION AREA SHALL BE THOROUGHLY SCARFIED BEFORE PLACEMENT OF THE MATERIAL THE SURFACE
SHALL HAVE MOSTURE ADDED ON IT SHALL BE COMPACTED BY HECESSARY SO THAT THE FRIST LAYER OF THE
MATERIAL CAN BE COMPACTED AND BOINDED TO THE COMPACTED AND BOINDED TO THE MATERIAL THE SURFACE
STANDING WAILER WHEN THE LIS BEING PLACED ON THEM.

### 2. FILL PLACEMENT

THE PLACING AND SPREADING OF FILL MATERIAL SHALL BE STARTED AT THE LOWEST POINT OF THE FOUNDATION AND THE FILL BROUGHT UP IN HORIZONTAL LAYERS OF 5" MAXIMUM COURSES AND COMPACT TO 99% MODIFIED PROCOTOR (ASTHUD 1657). THE FILL SHALL BE CONSTRUCTED IN CONTINUOUS HORIZONTAL LAYERS EXCEPT WHERE OPENINGS OR SECTIONALIZED FILLS ARE REQUIRED. IN THOSE CASES, THE SLOPE OF THE BOOMING SURFACES BETWEEN THE EMBANAMENT IN PLACE AND THE EMBANDANT OF THE PLACE SHALL BE INCREASED SHALL NOT BE STEEPER THAT 3 HORIZONTAL TO IVERTICAL. THE GOOD BOOMING SURFACE SHALL BE INFACED THE SAME AS THAT STEEDINGS FOR THE THE MATERIAL BOOMING SURFACE SHALL BE INFACED THE SAME AS


THE DISTRIBUTION AND GRADATION OF MATERIALS SHALL BE SUCH THAT NO LENSES, POCKETS, STREAMS, OR LAYERS OF MATERIAL DIFFER SUBSTANTIALLY IN TEXTURE OF GRADATION FROM THE SURROUNDING MATERIAL. IF IT IS INCESSARY TO USE MATERIALS OF VANION TEXTURE AND GRADATION, THE MORE UMFERVIOUS MATERIAL SHALL BE PLACED IN THE CENTER AND USE THE MATERIAL SHALL BE PLACED IN THE CENTER AND USE THE FILL. IF ZONED FILLS OF SUBSTANTIALLY DIFFERING MATERIALS ARE SPECIFIED, THE ZONES SHALL BE PLACED ACCORDING TO THE LINES AND GRADES SHOWN ON THE DRAWINGS. THE COMPLETE WORK SHALL DE LACED ACCORDING TO THE LINES AND GRADES SHOWN ON THE DRAWINGS. THE COMPLETE WORK SHALL DE LACED ACCORDING TO SHELL SHOWN OF THE DRAWINGS.


- MOISTURE CONTROL:
  THE MOISTURE CONTRINT OF THE FILL MATERIAL SHALL BE ADEQUATE FOR OBTAINING 95% COMPACTION.
  MATERIAL THAT IS TOO WET SHALL BE DRIED TO MEET THIS REQUIREMENT, AND MATERIAL THAT IS TOO DRY
  SHALL HAVE WATER ADDED AND MIXED UNTIL THE REQUIREMENT IS MET.
- COMPACTION: CONSTRUCTION EQUIPMENT SHALL BE OPERATED OVER THE AREAS OR EACH LAYER OF FILL TO INSURE THAT THE 95%, COMPACTION IS OBTAINED. SPECIAL EQUIPMENT SHALL BE USED IF NEEDED TO OBTAIN THE REQUIRED COMPACTION LEACH LAYER OF FILL SHALL BE COMPACTION LESCH LAYER OF FILL SHALL BE COMPACTED AS RECESSARY TO OBTAIN THAT DETISTING.
- 5. PROTECTION: A PROTECTIVE COVER OF VEGETATION SHALL BE ESTABLISHED ON ALL EXPOSED SURFACES OF THE EMBANKMENT, SPILLWAY, AND BORROW AREA IF SOIL AND CLIMATIC CONDITIONS FERMIT. IF SOIL OR CLIMATIC CONDITIONS PRECLUDE THE USE OF VEGETATION AND PROTECTION IS NEEDED. NON-VEGETATIVE MEANS, SUCH AS MULCHES OR GRAVEL, INA 9E USED. IN SOME PLACES, TEMPORARY VEGETATION MAY BE USED UNTIL CONDITIONS PERMIT ESTABLISHMENT OF PERMANENT VEGETATION.

### BERM MAINTENANCE


BERM - THE BERM SHALL BE INSPECTED ANNUALLY TO DETERMINE IF RODENT BURROWS, WET AREAS, OR EROSION OF THE FILL IS TAKING PLACE.

- VEGETATION THE VEGETATED AREAS OF THE STRUCTURE SHALL BE PROTECTED FROM DAMAGE BY FIRE, GRAZING, TRAFFIC, AND DENSE WEED GROWTH. LIME AND FERTILIZER SHALL BE APPLIED AS NECESSARY AS DETERMINED BY SOLT ESTS. TREES AND SHRUDS SHALL BE KEYD FOF THE EMBANKMENT AREAS.
- INLETS INLETS SHALL BE INSPECTED ANNUALLY AND AFTER EVERY MAJOR STORM. ACCUMULATED DEBRIS AND SEDIMENT SHALL BE REMOVED.
- OUTLETS OUTLETS ANALL BE INSPECTED ANNUALLY CAND AFTER EVERY MAJOR STORM. THE CONDITION OF THE OUTLET SHALL BE NOTED AND REPAIRS HAVE AS NECESSARY. IF ERDONE SHALL BE TAKEN TO STABLICE AND PROTECT THE AFFECTED AREA OF THE OUTLET.
- SEDIMENT SEDIMENT SHALL BE CONTINUALLY CHECKED IN THE BASIN. ANY SEDIMENT THAT ACCUMULATES IN FRONT OF THE INLET SHALL BE REMOVED AND PROPERLY DISPOSED OF.











SHED CRUSHED STONE


REFERENCE SPECIFICATION FROM THE MASSACHUSE ITS STORMAYATER ANABORON FOR DESIGN ORTHOR SERVICE UNTIL THE BMP HAS BEEN SEEDED AND TO SCOT FLACE THE SYSTEM HITO SERVICE UNTIL THE BMP HAS BEEN SEEDED AND TO SCONTIBUTING AREAS HAVE BEEN FULLY STABILIZED. DO NOT DISCHARGE SED MENT-LADE WATERS FROM CONSTRUCTION ACTIVITIES (RUMOFF, WATER FROM EXCAVATIONS) TO THE IMPELIATION BASIN DURING ANY STAGE OF CONSTRUCTION. DO NOT TRAFF CEMPOSED SOIL SURFACE WITH CONSTRUCTION EQUIPMENT. IF FEASIBLE, PERFORM EXCAVATIONS WITH EQUIPMENT POSITIONED OUTSIDE THE LIMITS OF THE INVESTIGATION COMPONENTS OF


**OUTLET CONTROL STRUCTURE** 












CDS-2015 DETAIL



BISTULUTION LIGHTS

A PROPERTY OF THE CONTROL OF THE MOOR AND FLOTATION PROVISIONS ARE SITE SPECIFIC DESIGN CONSIDERATIONS AND SHALL BE SEPCIFED BY ELAMBLES OF RECORD.

B CONTRACTOR TO PROVIDE COUPLEMENT WITH SUPFICIENT LETING AND REACH CAPACITY TO LIFT AND SET THE COS MARHOLE STRUCTURE. BE CONTROL TO REPORT OF THE COST MARHOLE STRUCTURE. CONTROL TO REPORT OF THE COST MARHOLE STRUCTURE.

CONTROL TO REPORT OF THE ADMINISTRATION OF THE COST MARKET STRUCTURE. SHOWN,

E CONTROL TO THE APPROPRIATE MASJUES TO ASSURE UNIT IS WATER TIGHT, HOLDING WATER TO FLOWLING INNERNATION THE CONTROL THE COST MARKET. THE COST MARKET TO THE COST MARKET. THE COST MARKET TO THE COST MARKET TO THE COST MARKET TO THE COST MARKET. THE COST MARKET TO THE COS

SITE SPECIFIC
DATA REQUIREMENTS PIPE DATA: 1E MATERIAL DUMETER
INLET PIPE 1 96.0 HDPE 15"
INLET PIPE 2-3 96.0 PVC 10"
OUTLET PIPE 96.0 HDPE 15" WIDTH HEIGHT OTES/SPECIAL REQUIREMENTS:

Date Construction Details - Pool Area **Jellystone Park Cranberry Acres** 20 Shoestring Road Carver, MA Assessors Map 124 Lot 13, Map 125 Lot 3A 83 Rockingham Rd, Unit 3 East Windham, NH 03087 (603) 647-8700 ENGINEERING Scale: As Shown Date: 9/20/2022 Sheet 8 of 9 Prepared for: NGR Cape Cod, LLC 38 Commerce Ave. SW Suite 200 NIEL M FLOR CIVIL No. 56928 Grand Rapids, MI 49503 Zoning Classification: Residential Agricultural

TRENCH DRAIN DETAIL

GRAVEL

GRAVEL BASE AS SPECIFIED

CROSS COUNTRY

IN EARTH

**TYPICAL TRENCH SECTION** 

FOR STORM DRAIN


**IN LEDGE** 

NNEL OR EQUAL

(DIAMETER VARIES)

SITE PLAN APPROVAL DATE:

CARVER PLANNING BOARD





M NORTHGATE RESORTS JELLYSTONE PARK CAMP RESORT POOL DESIGN DEVELOPMENT CARVER, MASSACHUSETTES **ADG** 

DESIGN GROUP

28 CENTRAL PARKWAY WEST CINCINNATI, OHIO 45202 513-651-9100 FAX 513-651-9101

LANDSC/ PLAN

SCALE: JUNE 28, 2022 DATE:

CHECKED BY: 222114

JOB# SHEET #

DD-1 ©2022 BDR DESIGN GROUP